

PRINTER CONFIGURATION	
Zebra Technologies	
ZTC S4M-200dpi ZPL	
10.0.....	DARKNESS
2 IPS.....	PRINT SPEED
+000.....	TEAR OFF
TEAR OFF.....	REMOVAL
REFLECTIVE.....	SENSOR TYPE
DIRECT-THERMAL.....	RIBBON
0660 DOTS.....	WIDTH
1199.....	LABEL LENGTH
AUTO.....	MAXIMUM LENGTH
GAP/NOTCH.....	MEDIA TYPE
CONNECTED.....	USB COMM.
BIDIRECTIONAL.....	PARALLEL COMM.
RS232.....	SERIAL COMM.
9600.....	BAUD
8 BITS.....	DATA BITS
NONE.....	PARITY
XON/XOFF.....	HOST HANDSHAKE
NONE.....	PROTOCOL
NORMAL MODE.....	HEXDUMP
<~> 7EH.....	CONTROL PREFIX
<^> 5EH.....	FORMAT PREFIX
<, > 2CH.....	DELIMITER CHAR
ZPL II.....	ZPL MODE
NO MOTION.....	MEDIA POWER UP
NO MOTION.....	HEAD CLOSE
DEFAULT.....	BACKFEED
+000.....	LABEL TOP
+0000.....	LEFT POSITION
DISABLED.....	REPRINT MODE
042.....	LABEL LEVEL
080.....	PAPER OUT
073.....	RIBBON OUT
017.....	PAPER GAIN
253.....	RIBBON GAIN
+10.....	LCD ADJUST
DPSMFXM.....	MODES ENABLED
	MODES DISABLED
832 8/MM FULL.....	RESOLUTION
V50.15.2Z <-.....	FIRMWARE
V23 ----- 3.....	HARDWARE ID
CUSTOMIZED.....	CONFIGURATION
3200k.....	.R: RAM
2048k.....	.E: ONBOARD FLASH
NONE.....	FORMAT CONVERT
NONE.....	ZEBRA NET II
2895 IN.....	NONRESET CNTR
21 IN.....	RESET CNTR1
21 IN.....	RESET CNTR2
7353 CM.....	NONRESET CNTR
54 CM.....	RESET CNTR1
54 CM.....	RESET CNTR2
LJ 38780.07RM003121.28300-001.K.vh..	

FIRMWARE IN THIS PRINTER IS COPYRIGHTED